

Robotic Total Station

Zoom80 Series



STReAM360

- Scout – Auto Find
- TRack – Auto Tracking
- AiM – Auto Targeting



Long Range Bluetooth

- High-Speed Data Link
- Reliable Connectivity
- License Free



Powerful Handheld

- Inbuilt Camera (3 M Pixel)
- Compass & Altimeter
- Long-range Bluetooth®

Zoom80 Series

Find your target, follow it and measure with constant accuracy – the three steps you repeat continuously with every single measurement. Now fully automatically done by your total station incorporating the new STReAM technology, that “works when you do”.



Scout360
Reflector Scan

TRack360
Continuous
Reflector Tracking

AiM360
Fully Automatic
Targeting

High
Resolution
Colour and
Touch Display

High Speed
Precision Drive

Long-range
Bluetooth®
Data Link

NavLight
Alignment Aid

accXess10
1,000m
Reflectorless

Long-range
Bluetooth®
Data Link

Camera
Compass
Altimeter
Windows
Mobile®

STReAM360

- **Scout** – finds your passive prism fully automatically
- **TRack** – continuously follows your prism
- **AiM** – highest precision aiming at your prism – any time, any condition with constantly high accuracy

Together with the additional incredible features such as 1,000 m reflectorless measurement capability, Navigation light and 1" accuracy, this robotic total station boosts your performance and accuracy all day long – day by day.

Zoom80S	One Man Servo TRack360, AiM360
Zoom80R	One Man Fully Robotic Scout360, TRack360, AiM360

Angle measurements

Accuracy	1" (0.3 mgon), 2" (0.6 mgon), 5" (1.5 mgon)
Display resolution	0.1" (0.1 mgon)
Method	Absolute, continuous, diametrical
Compensation	Quadruple axis

Distance measurements

Prism	3,500 m / 1 mm + 1.5 ppm
Long-range	10,000 m / 5 mm + 2 ppm
Reflectorless	1,000 m / 2 mm + 2 ppm *

Interfaces

Keyboard	Dual with 34 keys, illuminated
Display	¼ VGA colour LCD, touch screen
Data recording	Removable CF-card
Bluetooth	Device Class II, long-range
Interface	Serial & external power

Power supply

Internal battery	Removable Li-Ion 4.4 Ah / 7.4 V
Operating time	Typically 6 – 8 h
External power	11.5 V to 13.5 V DC

Physical specifications

Weight	5.5 kg when fully equipped
Operating temp.	-20°C to 50°C
Storage temp.	-40°C to 70°C
Protection class	IP54 dust- and waterproof
Humidity	95 %, non-condensing

Handheld

Operating system	Microsoft Windows Mobile®
Memory	Up to 16 GB
Ports	Serial, USB, expansion slot for long-range Bluetooth® cap, Bluetooth®, WLAN
Operating time	Up to 9 hours
Weight	2.7 kg (pole, prism, handheld)

* > 500 m: 4 mm + 2 ppm

All trademarks and trade names are those of their respective owners.

Distance meter (Reflector Mode): Laser class 1 in accordance with IEC 60825-1 resp. EN 60825-1; **Laser plummet:** Laser class 2 in accordance with IEC 60825-1 resp. EN 60825-1, **Distance meter (Reflectorless Mode accXess™):** Laser class 3R in accordance with IEC 60825-1 resp. EN 60825-1



Copyright GeoMax AG.
Illustrations, descriptions and technical specifications are not binding and may change.
III.MMXIII / 807264en