

# **LINERTEC**

## **A-100 Series Automatic Level**

### **A-128 / A-132**

- Reliable automatic compensator with the V-shaped suspension tape and air damper
- An easy-to-read horizontal circle
- Minimum focus distance of 0.6m
- Rugged construction usable even in a light rain
- Compact, light weight instrument (1.4 kg.)
- Quick-acting leveling screws for faster setups
- Attainable accuracy of  $\pm 2.0\text{mm}$  in 1km double run leveling



**Increase your  
work efficiency**



Model		A-128	A-132
<b>Telescope</b>	Image		Erect
	Magnification	28X	32X
	Effective aperture		36mm
	Minimum focus distance		0.6m
	Stadia ratio		1 : 100
	Stadia constant		0
<b>Automatic compensator</b>	Working range		±15'
	Setting accuracy		0.5"
	Standard deviation (1km double run leveling)		±2.0mm
<b>Sensitivity of vials</b>	Circular level sensitivity		10'/2mm
<b>Horizontal circle</b>	Graduation		360° or 400g
	Minimum division		1° or 1g
<b>Dimensions</b>	Instrument		230 (L) x 138 (W) x 140 (H) mm
	Carrying case		280 (L) x 185 (W) x 185 (H) mm
<b>Weight</b>	Instrument		1.4 kgs
	Carrying case		0.8 kgs

\* Specifications are subject to change without any notice

### Standard Configuration

- Hexagonal wrench
- Adjusting pin
- Plumb bob
- Instruction manual
- Carrying case



**TI Asahi Co., Ltd.**  
**International Sales Department**  
 4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi  
 Saitama, 339-0073 Japan  
 Tel.: +81-48-793-0118  
 Fax: +81-48-793-0128  
 E-mail: International@tiasahi.com

[www.tilinertec.com](http://www.tilinertec.com)

Your Official Linertec Dealer



The CE marking assures that this product complies with the requirements of the EC directive for safety.